



ALL CONTROLS

We measure it. **testo**



Bluetooth thermal hygrometer with App

testo 605i

Compact professional measuring instrument from the Testo Smart Tools series, for use with smartphones/tablets

Measurement of relative humidity and temperature

Measurement data analysis and transmission via Smart Probe App

Automatic calculation of dewpoint and wet bulb temperature via Smart Probe App

Space-saving and easy to transport



%RH

°C



Bluetooth +
App


The compact Bluetooth humidity measuring instrument testo 605i, in combination with a smartphone or tablet, is suitable for the measurement of air temperature and relative humidity in rooms and ducts. Together with the Bluetooth thermal anemometer testo 405i, cooling and heating performance can also be determined.

Users can read off their measurement values comfortably in the App installed on the end device. The App also enables the automatic determination of dewpoint and wet bulb temperature. All measurement data are presented either as a diagram or in tabular form. The measurement protocols can then be directly sent as PDF or Excel files.


Technical data/accessories

testo 605i

testo 605i, Bluetooth thermal hygrometer with App, incl. batteries and calibration protocol



Order no. 0560 1605



Testo Smart Tools App

The App turns your smartphone/tablet into the display of the testo 605i. The operation of the measuring instrument as well as the display of the measurement values take place by Bluetooth via the Testo Smart Probe App on your smartphone or tablet – independently of the measurement location. In addition to this, you can use the App to create measurement reports, add photos and comments to these, and send them by e-mail. For iOS and Android.

| Sensor type | Humidity – capacitive |
|-------------------|--|
| Measuring range | 0 to 100 %RH |
| Accuracy ±1 digit | ±(1.8 %RH 3 % of m.v.) at +25 °C (5 to 80 %RH) |
| Resolution | 0.1% RH |
| Sensor type | NTC |
| Measuring range | -20 to +60 °C |
| Accuracy ±1 digit | ±0.8 °C (-20 to 0 °C) ±0.5 °C (0 to +60 °C) |
| Resolution | 0.1 °C |

General technical data

| | |
|-----------------------|---|
| Compatibility | requires iOS 7.1 or newer / Android 4.3 or newer requires mobile end device with Bluetooth 4.0 |
| Storage temperature | -20 to +60 °C |
| Operating temperature | -20 to +50 °C |
| Battery type | 3 micro batteries AAA |
| Battery life | 280 hrs |
| Dimensions | 243 x 30 x 24 mm 100 mm probe shaft |
| Warranty | 2 years |

| Accessories | Order no. |
|---|-----------|
| testo Smart Case (VAC) for the storage and transport of testo 405i, testo 410i, testo 510i, testo 605i, testo 805i and testo 905i, dimensions 270 x 190 x 60 mm | 0516 0260 |
| ISO calibration certificate humidity, calibration points 11.3 %RH and 75.3 %RH at +25°C | 0520 0006 |
| ISO calibration certificate humidity, calibration point 75.3 %RH at +25°C | 0520 0096 |

1981 1764/msp/1/08.2015

Subject to change, including technical modifications, without notice.

Address:
4/25 Frederick Street
(Behind DPA Lighting)
Belmont, WA 6104



ALL CONTROLS

Phone: (08) 9277 4299
Fax: (08) 9277 5824

www.allcontrols.com.au